Tagra | Pro COB LED Strip Light | Long Run | 490 LEDs/m | 24V | IP20 | 8W/m | 2700K | 15M Reel

PC24-27KLR15M



Key Features

Light Colour: Very Warm White

Product Length: 15m

Lm/W (Up To): 93 Lm/W

Lm/m (Up To): 744 Lm/m

Run Length (Max): 15m

7 YEAR

Mechanical Data

Bend Direction	Vertical
Body Colour	White
Cable Both Ends	yes
Cable Length	500mm
Cable Sheath Material	PVC
Cable Weight	20AWG
LED Chip Type	COB
Copper Foil Weight	2oz
Cut Points	100mm

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

LEDs Per Metre	490
Min · Bend Radius	19mm
PCB Type	Flexible
Self Adhesive Brand	3M

Input

Input Voltage	24 - 24

Control

Dimmable	yes
Dimming Type	PWM

Electrical Data

Constant Voltage / Constant Current	CV
Current Max · @5 Metre	25M
Max · Run Length	15 m
Wattage Max · @1 Metre	8 W

Protection

Electrical Safety Class	III

Photometric Data

Lumens Per Metre	744 Lm/m
CCT	2700 - 2700
Bin Number	1
Colour Type	Single Colour
CRI	90
SDCM	<3
Lumens Per Watt	93Lm/W

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Environment

Application Environment	Indoor
Body Material	Plastic
Case Temperature Max · (tc)	65°C
Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior

Efficiency

Rated Life	5000 Hours

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions