LTECH | 24V | 240W | Constant Voltage | DALI DT6/DT8 CCT Dimmable LED Driver | IP20

LM-240-24-G2D2



Key Features

Dimming Range (min / max): 0.01 - 100%

Din Rail Compatible: No

Dimensions (mm): 50mm x 30mm x 380mm

5 YEAR

240W Max.

IP20

Mechanical Data

Body Colour	White
DIN Rail Compatible	No
Product Weight	300g

Input

Displacement Factor	0.7
Input Cable Shape	Round
Input Cable Sheath Material	Rubber
Input Control Connector Type	Bare end
Input Current	1.18A

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Input Current Type	AC
Input Terminal / Connector Type	Screw terminal
Input Voltage	220 - 240
Inrush Current	55A
Leakage Current	0.5mA

Output

Max · Output Current Per Channel	10A
No · of Control Channels	2
Output Current	3.125
Output Current Type	DC
Output Terminal/Connector Type	Screw terminal
Output Voltage	24 - 24
Rated Output Current	10A
Rated Power	240W

Control

Control Signal Input	DALI, Push dim
Control Signal Output	DALI
Default PWM Frequency	3600Hz
Dimmable	yes
Dimming Curve	Logarithmic%
Dimming Range	0.01 - 100
Dimming Type	Dimmable
Interface Type	DALI

Electrical Data

Constant Voltage / Constant Current	CV

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Protection

Electrical Safety Class	II
Over Current Protection	Yes
Over Current Protection Mode	Auto recovery
Over Temperature Protection	Yes
Over Temperature Protection Mode	Auto recovery
Over Voltage Protection	Yes
Over Voltage Protection Mode	Shut down
Short Circuit Protection	Yes
Short Circuit Protection Mode	Shut down

Environment

Application Environment	Indoor
Body Material	Plastic
Case Temperature Max · (tc)	86°C
Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior
Mounting Type	Surface Mounted

Efficiency

Average Active Efficiency	94
Efficiency @ 50% Load	94
Efficiency @ Full Load	94
No-Load Power Consumption	0.5W
Rated Life	100000 Hours
Standby Power Max ·	0.5 W

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions