Tagra | IP20 | 24V | Toning Essential | LED Strip Light | 60 LEDs p/m | 14.4W p/m | RGB | 50 Metres

TE24-RGB6050M



Key Features

Product Length: 50m

Lm/W (Up To): 41 Lm/W

Lm/m (Up To): 587 Lm/m

Run Length (Max): 5m

5 MTRS

3 YEAR

Mechanical Data

Bend Direction	Vertical
Body Colour	White
Cable Both Ends	yes
Cable Length	500mm
Cable Sheath Material	PVC
Cable Weight	20AWG
LED Chip Brand	RICHLUX
LED Chip Type	5050
Copper Foil Weight	2oz

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Cut Points	100mm
Entry Cable Direction	STRAIGHT
LED Pitch	100mm
LEDs Per Unit	6
LEDs Per Metre	60
LEDs Total	300
PCB Type	Flexible
Product Weight	150g
Self Adhesive Brand	3M

Input

Input Voltage	24 - 24

Control

Dimmable	yes
Dimming Type	PWM

Electrical Data

Constant Voltage / Constant Current	CV
Current Max · @5 Metre	3M
Current Typ · @Max Run Length	3 A
Max · Run Length	5 m
Wattage Max · @1 Metre	14.4 W
Wattage Typ · @1 Metre	14.4 W
Wattage Typ · @5 Metre	72 W
Wattage Typ · @Max Run Length	72 W

Protection

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Electrical Safety Class	III

Photometric Data

Wavelength Blue	465 - 467.5
Wavelength Green	520 - 523
Wavelength Red	623 - 620
Lumens Per Metre	587 Lm/m
Bin Number	1
Colour Type	RGB
SDCM	<5
Lumen Total	2641.5Lm
Lumens Per Watt	41Lm/W

Environment

Anti-Yellowing	yes
Application Environment	DOSMETIC, COMMERICAL, RESIDENTAL
Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior
Saltwater Resistant	yes
UV Resistant	yes

Efficiency

L70B50	150000 Hours
L80B10	78000 Hours
L90B10	37000 Hours
Lumen Maintenance Factor	99.26
Rated Life	50000 Hours
Survival Factor	1

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Switch Cycles	25000

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions