Tagra | Pixel COB LED Strip Light | 720 LEDs p/m | 30 pixels p/m | 24V | IP20 | 31Wp/m | RGB | 20M Reel

TD24-RGBCOB20M



Key Features

Product Length: 20m

Lm/W (Up To): 20 Lm/W

Lm/m (Up To): 1060 Lm/m

Lm/m (Red): 220 Lm/m

Run Length (Max): 5m

5 MTRS

2 YEAR

Mechanical Data

Bend Direction	Vertical
Body Colour	White
Cable Length	500mm
LED Chip Type	COB
Copper Foil Weight	3oz
Cut Points	33.33mm
LEDs Per Metre	720
Pixels Per Metre	30
Product Weight	120g

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Input	
Input Voltage	24 - 24
Control	
Default PWM Frequency	2000Hz
Dimmable	yes
IC Type	WS2811
Electrical Data	
Current Max · Blue @1 Metre	1.3 A
Current Max · Green @1 Metre	1.3 A
Current Max · Red @1 Metre	1.3 A
Current Typ · @Max Run Length	6.5 A
Max · Run Length	5 m
Wattage Max · @1 Metre	22.5 W
Photometric Data	
Wavelength Blue	460 - 470
Wavelength Green	515 - 525
Wavelength Red	630 - 620
Lumens Per Metre	1060 Lm/m
Colour Type	RGB
Lumens Per Metre (Blue)	179Lm/m
Lumens Per Metre (Red)	220Lm/m
Lumens Per Watt	20Lm/W
Environment	
Application Environment	Indoor

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions