Tagra | Essential LED Strip Light | 120 LEDs p/m | 24V | IP20 | 9.6Wp/m | 2700K | 50M Reel

ES24-27K-120-50M-80



Key Features

24V

9.6 Watts p/m

8mm width

Up to 1040 Lumens Per Metre

IP20

3 Year Warranty

50mm Cut Points

Available in 2700K, 3000K, 4000K and 6000K

Also Available in Cut to Order


Bulk discounts available on 50m reels - please contact us for details

Mechanical Data

Body Colour	White
Bend Direction	Vertical
Cable core count	2
Cable Length	500
Copper Foil Weight	2
Cut Points	50
LEDs Per Metre	120
Product Weight	645
Product Dimensions	50000x8x2 mm

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Dimensions



Input

Input Current Type	DC

Control

Dimmable	Yes

Electrical Data

Max · Run Length	8
Wattage Max · @1 Metre	9.6

Photometric Data

Beam Angle	120
Bin Number	2
Colour Type	Single Colour
CRI	80

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Lumens Per Metre	902.4
Lumens Per Watt	94
SDCM	5
Lumen Total	45000

Environment

Ingress Protection (IP)	20
Interior or Exterior Use	INTERIOR

Efficiency

Energy Efficiency Class	F

Packaging & Shipping

Battery Included	No
Glue Included	No
Volume	2829400

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions