Tagra | Essential COB LED Strip Light | 320 LEDs p/m | 24V | IP65 | 8Wp/m | 2700K | 50M Reel

EC24-27K50M65



Key Features

Light Colour: Very Warm White

Product Length: 50m

Lm/W (Up To): 65 Lm/W

Lm/m (Up To): 520 Lm/m

Run Length (Max): 5m

5 MTRS

2 YEAR

Mechanical Data

Bend Direction	Vertical
Body Colour	White
Cable Both Ends	yes
Cable Length	500mm
Cable Sheath Material	PVC
Cable Weight	20AWG
LED Chip Brand	SANAN
LED Chip Type	FLIP-CHIP
Copper Foil Weight	20oz

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Cut Points	50mm
Entry Cable Direction	REAR
LEDs Per Unit	16
LEDs Per Metre	320
LEDs Total	1600
Min · Bend Radius	60mm
Product Weight	380g
Self Adhesive Brand	3M
Self Adhesive Model Number	55230H

Input

Input Voltage	24 - 24

Control

Dimmable	yes
Dimming Type	0-10V, TRIAC, PWM, DALI

Electrical Data

Constant Voltage / Constant Current	CV
Current Max · @5 Metre	1.44M
Current Typ · @Max Run Length	1.31 A
Max · Run Length	5 m
Wattage Max · @1 Metre	8 W
Wattage Typ · @1 Metre	7.2 W
Wattage Typ · @5 Metre	31.5 W
Wattage Typ · @Max Run Length	31.5 W

Protection

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Electrical Safety Class	III

Photometric Data

Wavelength	580.6nm
Lumens Per Metre	520 Lm/m
CCT	2700 - 2700
Bin Number	2
Colour Type	Single Colour
CRI	90
SDCM	<5
Lumen Total	2550Lm
Lumens Per Watt	65Lm/W
Luminous Intensity	124cd
Peak Luminous Intensity	124cd

Environment

Application Environment	DOMESTIC, HOPSITALITY, COMMERICAL
Body Material	PLASTIC
Ingress Protection (IP)	IP65
Interior or Exterior Use	INTERIOR

Efficiency

Energy Efficiency Class	G
L70B50	36000 Hours
L80B10	36000 Hours
L90B10	24000 Hours
LM80	6000Hours
Lumen Maintenance Factor	0.9707

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Rated Life	36000 Hours
Survival Factor	0.9
Switch Cycles	10000

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions