ITM000539



36W Max.

3 YEAR

Key Features

- **Rated Power:** 36
- **Din Rail Compatible:** yes
- **Dimensions (mm):** 90mm x 58mm x 35mm

Mechanical Data			
Body Colour	White	DIN Rail Compatible	yes
Product Weight	78g		

Electrical Data	
Constant Voltage / Constant Current	CV

Input Data			
Input Current	0.88A	Input Current Type	AC
Input Frequency	50 - 60	Input Terminal / Connector Type	Screw terminal
Input Voltage	90 - 264	Inrush Current	45A
Leakage Current	0.5mA	No · of Input Terminals	1

Output Data

Control Data	
Dimming Type	Non-Dimmable

Environment Data			
Body Material	Plastic	Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior	Mounting Type	Din Rail

Protection Data			
Electrical Safety Class	II	Over Current Protection	yes
Over Current Protection Mode	Auto recovery	Over Temperature Protection	yes
Over Temperature Protection Mode	Hiccup	Over Voltage Protection	yes
Over Voltage Protection Mode	Shut down	Short Circuit Protection	yes
Short Circuit Protection Mode	Shut down		

Efficiency Data	
Average Active Efficiency	89

Disclaimer

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions.