ITM001537



5 YEAR

IP20

Key Features

- **Colour Control Type:** Single Colour, CCT Tunable White, RGB, RGBW, RGBCCT Tunable White
- **Input Terminal / Connector Type:** MICRO USB SOCKET, DC12-24V POWER SOCKET
- **Control Distance:** 15m
- **Din Rail Compatible:** No

Mechanical Data			
Body Colour	White	DIN Rail Compatible	No
Product Weight	49g	SD Card Slot	No

Electrical Data	
Constant Voltage / Constant Current	CV

Input Data			
Input Current	0.36A	Input Current Type	DC
Input Terminal / Connector Type	MICRO USB SOCKET, DC12-24V POWER SOCKET	Input Voltage	5 - 5

Control Data			
Colour Control Type	Single Colour, CCT Tunable White, RGB, RGBW, RGBCCT Tunable White	Control Distance (barrier-free)	15m
Control Signal Input	RF 2.4GHz	Dimming Range	0 - 100
DIP Switch	No	No · of Scenes	1

Environment Data			
Application Environment	DOMESTIC	Body Material	Plastic
Case Temperature Max · (tc)	55°C	Ingress Protection (IP)	IP20
Mounting Type	Surface Mounted		

Protection Data			
Electrical Safety Class	III	Over Current Protection	No
Over Temperature Protection	No	Over Voltage Protection	No
Reverse Polarity Protection	No	Short Circuit Protection	No

Efficiency Data	
Rated Life	50000 Hours

Packaging & Shipping Data	
Fixings Included	No

Disclaimer

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions.