ITM002898



5 YEAR | IP20 | 12V-36V

Key Features

- **Colour Control Type:** Single Colour
- **Input Terminal / Connector Type:** Screw terminal
- **Output Terminal / Connector Type:** Screw terminal
- **Control Distance:** 30m
- **Din Rail Compatible:** No

Mechanical Data			
Body Colour	White	DIN Rail Compatible	No
Product Weight	73g		

Electrical Data	
Constant Voltage / Constant Current	CV

Input Data			
Input Current	10.5A	Input Current Max ·	10.5A
Input Current Type	DC	Input Terminal / Connector Type	Screw terminal
Input Voltage	12 - 24		

Output Data

Control Data			
Colour Control Type	Single Colour	Control Distance (barrier-free)	30m
Control Signal Input	RF, Push dim	Default PWM Frequency	2000Hz
Dimming Curve	Logarithmic%	Dimming Range	0 - 100
DIP Switch	No	Interface Type	WIFI, RF

Environment Data			
Body Material	Plastic	Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior	Mounting Type	Surface Mounted

Protection Data			
Electrical Safety Class	III	Over Temperature Protection	Yes
Reverse Polarity Protection	Yes	Short Circuit Protection	Yes

Disclaimer

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions.