ITM004223



Key Features

- **Colour Control Type:** CCT Tunable White
- **Dimming Range (min / max):** 0 - 100%
- **Control Distance:** 20m

Mechanical Data			
Body Colour	White	DIN Rail Compatible	No
Product Weight	152g		

Input Data			
Input Current Type	AC	Input Terminal / Connector Type	Screw
Input Voltage	100 - 240		

Output Data

Control Data			
Colour Control Type	CCT Tunable White	Control Distance (barrier-free)	20m
Control Signal Input	0-10	Control Signal Output	0/1-10V
Dimming Range	0 - 100	DIP Switch	yes

Environment Data			
Application Environment	Domestic, hospitality, commercial	Body Material	Plastic
Case Temperature Max · (tc)	90°C	Ingress Protection (IP)	IP20
Interior or Exterior Use	Interior	Mounting Type	Surface Mounted

Protection Data	
Electrical Safety Class	II

Efficiency Data			
Rated Life	30000 Hours	Standby Power Max ·	0.5 W
Standby Power Typ ·	0.5	Startup Time	0.5 Secs

Disclaimer

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions.