Tagra | Pro LED Neon Flex | Dual 10 | Cut Anywhere | 10x10mm | 2700K | 24V | IP67 | 8.8Wp/m | 5M Kit - OLD

NEONDUAL1010-5MKIT-27K



Key Features

Product Length: 5m

Light Colour: Very Warm White

Run Length (Max): 5m

5 YEAR

5 MTRS

Mechanical Data

Bend Direction	Dual
Body Colour	White
Cable Both Ends	Yes
Cable Length	1000mm
Cable Sheath Material	Silicone
Cable Weight	20AWG
Cut Points	0mm
Entry Cable Direction	Rear
LED Chip Type	2216

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

LEDs Per Metre	240
LEDs Per Unit	2
LEDs Total	1130

Input

Input Voltage	24 - 24

Control

Control Signal Input	PWM
Dimmable	Yes
Dimming Type	PWM

Electrical Data

Constant Voltage / Constant Current	CV
Current Max · Rated	1.65 A
Current Typ · @Max Run Length	1.49 A
Max · Run Length	5 m
Wattage Max · @1 Metre	8.8 W
Wattage Typ · @1 Metre	8 W
Wattage Typ · @5 Metre	40 W
Wattage Typ · @Max Run Length	40 W

Protection

Electrical Safety Class	III

Photometric Data

CCT	2700 - 2700
Colour Type	Single Colour
CRI	90

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Lumen Total	2030Lm
Lumens Per Metre	406 Lm/m
Lumens Per Watt	51Lm/W
R9 Value	63
SDCM	<3

Environment

Anti-Yellowing	Yes
Application Environment	Furniture, Cabinetry, Retail, Commercial
Body Material	Silicone
Case Temperature Max · (tc)	65°C
Ingress Protection (IP)	IP67
Interior or Exterior Use	Interior or Exterior
Saltwater Resistant	Yes
Solvent Resistant	Yes
UV Resistant	Yes

Efficiency

L70B50	50 Hours
Rated Life	50000 Hours

Packaging & Shipping

Emery Paper Included	yes
End Caps Included	yes
Kit	yes
Mounting Brackets Included	yes

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions