Tagra | Joinery LED Strip Light | 420 LEDs p/m | 24V | IP20 | 10Wp/m | 2700K | 2.5M Reel

PC24-27K-2.5M-90



Key Features

Product width: 4 mm- **Lm/m (up to)**: 810 Lm/m- **Lm/W (up to)**: 81 Lm/W- **CRI**: 90± **Lightsource SDCM**: ≤3- **Run length (max)**: 2.5 m- **Available Colours**: 2700K, 3000K, 4000K, 6500K- **Warranty**: 3 Years

Mechanical Data

Bend Direction	Vertical
Body Colour	White
Cable core count	2
Cable Length	500
Copper Foil Weight	2
Cut Points	16.67
LEDs Per Metre	420
Product Weight	20
Product Dimensions	2500x4x2 mm

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Dimensions



Input

Input Current Type	DC

Control

Dimmable	Yes

Electrical Data

Max · Run Length	2.5
Wattage Max · @1 Metre	10

Photometric Data

Beam Angle	140
Colour Type	Single Colour
CRI	90
Lumen Total	1525

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Bin Number	1
Lumens Per Metre	610
Lumens Per Watt	61
R9 Value	52
SDCM	3

Environment

Ingress Protection (IP)	20
Interior or Exterior Use	INTERIOR

Efficiency

Energy Efficiency Class	G

Packaging & Shipping

Battery Included	No
Glue Included	No
Volume	968968

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions