PPS24-4K-140-5M-90



Key Features

Product width: 8 mm- **Lm/m (up to)**: 901.6 Lm/m- **Lm/W (up to)**: 98 Lm/W- **CRI**: 90± **Lightsource SDCM**: ≤5- **Run length (max)**: 5 m- **Available Colours**: 2700K, 3000K, 4000K, 6500K- **Warranty**: 3 Years




Mechanical Data

Body Colour	White
Bend Direction	Vertical
Cable Length	500 mm
Cut Points	7.14
LEDs Per Metre	140
Product Weight	69 g
Cable core count	2
Product Dimensions	5000x8x2 mm

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Dimensions



Input

Input Cable Weight	20 AWG
Input Current Type	DC
Input Voltage	24 V

Output

Output Current Type	DC

Control

Dimmable	Yes

Electrical Data

Max · Run Length	5 m
Wattage Max · @1 Metre	9.2 W

Photometric Data

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Colour Type	Single Colour
CRI	90
Lumens Per Metre	900 Lm/m
Lumens Per Watt	94 Lm/W
SDCM	5
CCT	4000 K

Environment

Application Environment	Indoor
Ingress Protection (IP)	20
Interior or Exterior Use	Interior

Efficiency

Energy Efficiency Class	F

Packaging & Shipping

Battery Included	No
Volume	0 ml
Glue Included	No

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions