Syndeo by Tagra | LED Strip Light | Free Cut COB | 320 LED's p/m | 24V | IP20 | 11.2W p/m | 2700K | 5M Reel

PPS24-27KFC5M



Key Features

Syndeo Plug & Play Compatible

Up to 1200 Lumens per metre

IP20

8mm Width

7 Year Warranty

Cut Anywhere

Available in 5 Metres

Available in 2700K, 3000K, 4000K & 6000K



Mechanical Data

Bend Direction	Vertical
Cable Length	5000 mm
Cable Sheath Material	PVC
Cable Weight	22 AWG
LED Chip Type	COB
Copper Foil Weight	2 oz
LEDs Per Metre	320
LEDs Total	1600
Min · Bend Radius	20 mm

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

PCB Type	Flexible
Self Adhesive Brand	3M
Self Adhesive Model Number	300LSE
Body Colour	White
Product Dimensions	5000x8x3 mm

Dimensions



Input

Input Voltage	24 V

Control

Dimming Type	PWM, 0-10V, TRIAC, DALI, DMX

Electrical Data

Constant Voltage / Constant Current	CV
Wattage Typ · @1 Metre	11.2 W

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Wattage Typ · @5 Metre	44.8 W
Max · Run Length	5 m

Protection

Electrical Safety Class	III

Photometric Data

Beam Angle	150 °
Bin Number	1
Colour Type	Single Colour
CRI	90
Lumen Total	6375 Lm
Lumens Per Metre (White)	1275 Lm/m
SDCM	3
Lumens Per Metre	1086 Lm/m
Lumens Per Watt	97 Lm/W
R9 Value	77
CCT	2700 K

Environment

Application Environment	Indoor
Ingress Protection (IP)	20
Interior or Exterior Use	Interior

Efficiency

Energy Efficiency Class	F
L70B50	50000 Hours
Rated Life	50000 Hours

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions