Syndeo By Tagra | Joinery LED Neon Flex | Mini 4 | 4x10mm | 3000K | 24V | IP65 | 7.2Wp/m | 5 Metre Kit

PPS24-3K4105MKIT



Key Features

Product Dimensions (mm): L5000xW4xH10.- **Bend direction:** Horizontal- **Lm/m:** 270 Lm/m- **Lm/W:** 38 Lm/W- **Run length (max):** 5 m- **Light colour:** 2700 K- **Warranty:** 3 Years, 5 Years




Mechanical Data

Body Colour	White
Bend Direction	Horizontal
Cable Both Ends	1
Cable Length	500 mm
Cable Sheath Material	Silicone
Cable Weight	22 AWG
LED Chip Brand	Sanan
LED Chip Type	SMD2835

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Copper Foil Weight	4 oz
Cut Points	5.95 mm
Entry Cable Direction	Rear
LED Pitch	5.95 mm
LEDs Per Unit	1
LEDs Per Metre	160
LEDs Total	800
Min · Bend Radius	60 mm
Pixels Per Metre	12
Product Weight	300 g
Product Dimensions	5000x4x10 mm

Dimensions



Input

Input Voltage	24 V

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Control

Control Signal Input	RF
Dimming Type	PWM

Electrical Data

Constant Voltage / Constant Current	CV
Current Max · @1 Metre	0.33
Current Max · @5 Metre	1.65
Current Typ · @1 Metre	0.3
Current Typ · @5 Metre	1.5
Current Typ · @Max Run Length	1.5 A
Current Max · Rated	1.5 A
Max · Run Length	5 m
Wattage Max · @1 Metre	7.9 W
Wattage Typ · @1 Metre	7.2 W
Wattage Typ · @5 Metre	36 W
Wattage Typ · @Max Run Length	36 W

Protection

Electrical Safety Class	III

Photometric Data

Beam Angle	120 °
Bin Number	1
Colour Type	Single Colour
CRI	90
Luminous Intensity	92.44 cd

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions

Lumen Total	840 Lm
Lumens Per Metre	270 Lm/m
Lumens Per Watt	38 Lm/W
Wavelength	590 nm
Peak Luminous Intensity	92.44 cd
SDCM	< 3
R9 Value	55
CCT	3000 K
Wavelength Blue	465 - 470 nm

Environment

Application Environment	Signage, Retail, Events, Low-Mid Level Facadee
Body Material	Silicone
Ingress Protection (IP)	IP65
Interior or Exterior Use	Interior or Exterior

Packaging & Shipping

End Caps Included	Yes
Kit	Yes
Glue Included	Yes
Emery Paper Included	Yes
Mounting Brackets Included	Yes

Ultra LEDs have taken reasonable care to ensure that the information in this datasheet is accurate at time of publication however it should be noted that all specifications are subject to tolerance. Descriptive specifications such as colour are subjective. Ultra LEDs reserve the right to update specifications without notice. The information in the datasheet may only be relied on by customers of Ultra LEDs in accordance with applicable terms and conditions