MICRO TOP VIEW 04X10MM LED NEON FLEX, NEUTRAL WHITE 4000K, 12V, IP65 (5M KIT)

SKU: NEONTOPMICRO410/5MKIT-NW



K Dimmable CRI CUS Reach


TECHNICAL INFORMATION

Neon Specifications

SKU Code	NEONTOPMICRO410/5MKIT-NW
Voltage	12V
Watts p/M	7.9W p/M
Colour Temp	Neutral White 4000K
Lumens p/M	300LM
Min Bend Radius	30mm
CRI	80
Dimensions	4mm x 10mm x 5000mm
IP Rating	IP65
IK Rating	IK06
Cut Points	Every 17mm
Operating Temp	-20°C to +45°C
Lifespan	Up to 36000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	3 Years

Driver Requirements

1 Metre	> 8W
2 Metres	> 16W
3 Metres	> 24W
4 Metres	> 32W
5 Metres	> 40W
6 Metres	> 48W
7 Metres	> 56W
8 Metres	> 64W
9 Metres	> 72W
10 Metres	> 80W



ULTRA LEDS



FEATURES & BENEFITS

- Introducing our smallest, most flexible LED Neon. The 4x10mm offers a non-spotting, fully diffused light output. The splashproof silicon coating is fully flexible with a bend radius of up to 30mm
- High quality, high brightness
- Suitable for indoor and outdoor use
- Salt Water Resistant
 Solvent Resistant
 UV Resistant
 Flame Resistant

DESCRIPTION

Introducing our smallest, most flexible LED Neon yet. The 4x10mm offers a non-spotting, fully diffused light output. The splashproof silicon coating is fully flexible with a bend radius of up to 30mm, making it ideal for use in signage and display installations both indoors and outdoors.

Neon Flex is a durable fully diffused linear light perfect for furniture and signage manufacturers thanks to it's easy to install plug and play technology. This neon can be cut easily to your desired lengths at the allocated cut points. Maximum length at any time is 5 metres before visible voltage drops occur.

This 5m kit comes with everything you will need for installation, including mounting brackets, endcaps, silicone sealant and plug and play cable compatible with our Syndeo Easy to Use range. N.B. Syndeo driver not included.

Neon Flex can be dimmed via mains dimming, DALI, DMX, RF or 0-10 controllers.

Our 4x10 Micro Neon Flex comes with a 3 year guarantee as standard on indoor installations (1 year on outdoor installations).

GALLERY

