

PRODUCT DATASHEETENDURA STYLE UpDown Puck 13 W DG

ENDURA STYLE UPDOWN PUCK | Luminaire with direct up and down light output



AREAS OF APPLICATION

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

PRODUCT BENEFITS

- Easy and quick installation
- Energy-efficient thanks to LED technology

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available in two housing colors



TECHNICAL DATA

Electrical data

Nominal wattage	12.50 W	
Operating mode Electronic control gear (ECG)		
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	


Photometrical data

Color temperature	3000 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Luminous flux	980 lm
Luminous efficacy	75 lm/W

Light technical data

Beam angle	110°

Dimensions & weight



Length	131.0 mm
Width	91.0 mm
Height	110.0 mm
Product weight	630.00 g

Colors & materials

Body material	Aluminum	
Product color	Dark gray	
Housing color	Dark gray	
Cover material	Polymethylmethacrylate (PMMA)	

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Number of switching cycles	15000
Lifespan	30000 h

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075205567	Folding carton box 1	124 mm x 154 mm x 166 mm	670.00 g	3.17 dm ³
4058075205574	Shipping carton box 6	385 mm x 170 mm x 355 mm	4252.00 g	23.23 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.